

ASE ComCenter II Series

The ComCenter II Series provides voice and/or data communications anywhere in the world. A versatile Ethernet port allows network connectivity for global satellite data transfer and remote system control. Designed to meet a wide variety of applications and system installations, the ComCenter II is available in two main configurations - Voice and Data, or Data only - each with optional configurations and accessories such as privacy handset and GPS.

Overview

The ASE ComCenter II is a high-quality data and voice terminal for the Iridium network that offers excellent voice quality. This is a reliable, robust satellite communications terminal with:

- Top voice quality of Iridium's satellite network
- Simple installation and setup
- Cable to POTS equipment up to 3km away
- IP Addressable for data connects direct or using router, and Built-in diagnostic tools.



The ASE ComCenter II also provides the following:


Text Messaging

- Exclusive ASE SatChat text messaging
- Color-coded incoming and outgoing messaging
- Automatic system status messaging

Voice Features

- POTS interface for extended voice links
- ASE 'SmartDial'
- RJ-45 intelligent privacy handset interface for voice or texting
- Supports pre-paid scratch and post-paid Manager's cards
- Pre-assigned PIN(s) to protect post-paid usage

Space for everyone





Data Features

- Data connectivity using Ethernet infrastructure
- IP setup utilities simplifies installation
- Real-time and historical diagnostic logs
- Exclusive ASE SatChat text messaging
- Color-coded incoming and outgoing messaging

Features

POTS (RJ11) Connect:

- Connects to an analog phone (single or PBX) including multi-handset wireless phones. Use of a cordless phone with expandable handsets can provide up to eight units within a two-mile range (unobstructed) from the base station.

Ethernet (RJ45) Connect:

- Embedded web page for system setup, diagnostics and status.
- ASE SatChat embedded text messaging.
- Connects to Internet and automatically establishes a PPP session with Iridium ISP.
- Works with any web browser and is NOT operating system dependent.
- Configurable as DHCP Client or DHCP Server for integration into large or small networks.

Certifications

- Iridium certified product.
- Additional approvals and certifications include FCC, CE and IEC 60945.

Specifications

- Length: 9 in.
- Width: 5 in.
- Depth: 2.5 in.
- Weight: 2 lbs.
- Power: 10-36VDC, Universal AD/DC adapter included.
- Exposure: Indoor per IEC60945.



Space for everyone

